



Main

Range	Compact
Range of product	INS250 INS320...630 INS40...160 INS630b...2500 INSJ400 INV100...250 INV320...630 INV630b...2500 NG160 NG160NA NR100...250 NR400...630 NSC100 NSX100...250 NSX400...630 Easypact CVS100...250 Easypact CVS400...630 INSE80 PowerPact multistandard
Device short name	OF SD SDE SDV
Product or component type	Auxiliary contact
Range compatibility	Compact Compact NS1600b...3200 Compact Compact NS630b...1600 Compact Compact NSX Compact Compact NG Compact Compact NR Easypact EasyPact CVS Compact Compact INS Compact Compact INSE Compact Compact INSJ Compact Compact INV
Offer type	C4 C5
Signal contacts composition	1 NO/NC

Complementary

Auxiliary contacts type	Standard
-------------------------	----------

Auxiliary contacts operation	Early-break Early-make
Mounting mode	Clip-on
[I _{th}] conventional free air thermal current	6 A
[I _e] rated operational current	Utilisation category AC-12 : 6 A network: AC 50/60 Hz at 110 V Utilisation category AC-12 : 6 A network: AC 50/60 Hz at 220/240 V Utilisation category AC-12 : 6 A network: AC 50/60 Hz at 24 V Utilisation category AC-12 : 6 A network: AC 50/60 Hz at 380/440 V Utilisation category AC-12 : 6 A network: AC 50/60 Hz at 48 V Utilisation category AC-12 : 6 A network: AC 50/60 Hz at 480 V Utilisation category AC-12 : 6 A network: AC 50/60 Hz at 660/690 V Utilisation category AC-15 : 0.1 A network: AC 50/60 Hz at 660/690 V Utilisation category AC-15 : 1.5 A network: AC 50/60 Hz at 480 V Utilisation category AC-15 : 2 A network: AC 50/60 Hz at 380/440 V Utilisation category AC-15 : 4 A network: AC 50/60 Hz at 220/240 V Utilisation category AC-15 : 5 A network: AC 50/60 Hz at 110 V Utilisation category AC-15 : 6 A network: AC 50/60 Hz at 24 V Utilisation category AC-15 : 6 A network: AC 50/60 Hz at 48 V Utilisation category DC-12 : 0.3 A network: DC at 250 V Utilisation category DC-12 : 0.6 A network: DC at 110 V Utilisation category DC-12 : 2.5 A network: DC at 48 V Utilisation category DC-12 : 6 A network: DC at 24 V Utilisation category DC-14 : 0.03 A network: DC at 250 V Utilisation category DC-14 : 0.05 A network: DC at 110 V Utilisation category DC-14 : 0.2 A network: DC at 48 V Utilisation category DC-14 : 1 A network: DC at 24 V
Minimum load	100 mA at 24 V
Product compatibility	PowerPact H-Frame PowerPact J-Frame PowerPact L-Frame
Accessory / separate part category	Spare part Compact NS630b...1600 Spare part Compact NS1600b...3200

Contractual warranty

Warranty period	18 months
-----------------	-----------