

SIMATIC DP, 5 ELECTRON. MODULES FOR ET 200S, 4 DO  
STANDARD DC 24V/0.5A, 15 MM WIDTH 5 PIECES PER  
PACKAGING UNIT

|                                             |                                                              |
|---------------------------------------------|--------------------------------------------------------------|
| <b>Supply voltage</b>                       |                                                              |
| Reverse voltage protection                  | Yes; when using the same load voltage as on the power module |
| <b>Load voltage L+</b>                      |                                                              |
| • Rated value (DC)                          | 24 V; From power module                                      |
| • Reverse polarity protection               | Yes                                                          |
| <b>Input current</b>                        |                                                              |
| from load voltage L+ (without load), max.   | 5 mA; Per channel                                            |
| from backplane bus 3.3 V DC, max.           | 10 mA                                                        |
| <b>Power loss</b>                           |                                                              |
| Power loss, typ.                            | 0.8 W                                                        |
| <b>Address area</b>                         |                                                              |
| <b>Address space per module</b>             |                                                              |
| • with packing                              | 2 bit                                                        |
| • without packing                           | 1 byte                                                       |
| <b>Digital outputs</b>                      |                                                              |
| Number of digital outputs                   | 4                                                            |
| <b>Short-circuit protection</b>             |                                                              |
| • Response threshold, typ.                  | 0.7 to 1.5 A                                                 |
| Limitation of inductive shutdown voltage to | -55 to -60 V                                                 |
| Controlling a digital input                 | Yes                                                          |
| <b>Switching capacity of the outputs</b>    |                                                              |
| • on lamp load, max.                        | 5 W                                                          |
| <b>Load resistance range</b>                |                                                              |
| • lower limit                               | 48 $\Omega$                                                  |
| • upper limit                               | 3 400 $\Omega$                                               |
| <b>Output voltage</b>                       |                                                              |
| • for signal "1", min.                      | L+ (-1 V)                                                    |
| <b>Output current</b>                       |                                                              |
| • for signal "1" rated value                | 0.5 A                                                        |
| • for signal "0" residual current, max.     | 0.3 mA                                                       |
| <b>Output delay with resistive load</b>     |                                                              |
| • "0" to "1", max.                          | 100 $\mu$ s                                                  |
| • "1" to "0", max.                          | 300 $\mu$ s                                                  |

|                                                                 |                 |
|-----------------------------------------------------------------|-----------------|
| Parallel switching of two outputs                               |                 |
| • for uprating                                                  | No              |
| • for redundant control of a load                               | Yes; per module |
| Switching frequency                                             |                 |
| • with resistive load, max.                                     | 100 Hz          |
| • with inductive load, max.                                     | 2 Hz            |
| • on lamp load, max.                                            | 10 Hz           |
| Cable length                                                    |                 |
| • shielded, max.                                                | 1 000 m         |
| • unshielded, max.                                              | 600 m           |
| Isochronous mode                                                |                 |
| Isochronous operation (application synchronized up to terminal) | No              |
| Interrupts/diagnostics/status information                       |                 |
| Diagnostic functions                                            | No              |
| Diagnostics indication LED                                      |                 |
| • Status indicator digital output (green)                       | Yes             |
| Parameter                                                       |                 |
| Remark                                                          | 1 byte          |
| Potential separation                                            |                 |
| Potential separation digital outputs                            |                 |
| • between the channels                                          | No              |
| • between the channels and backplane bus                        | Yes             |
| Permissible potential difference                                |                 |
| between different circuits                                      | 75 V DC/60 V AC |
| Isolation                                                       |                 |
| Isolation tested with                                           | 500 V DC        |
| Dimensions                                                      |                 |
| Width                                                           | 15 mm           |
| Height                                                          | 81 mm           |
| Depth                                                           | 52 mm           |
| Weights                                                         |                 |
| Weight, approx.                                                 | 40 g            |
| last modified:                                                  | 04/23/2018      |