

SIMATIC S7-300, CPU 314C-2 DP Compact CPU with MPI, 24 DI/16 DO, 4 AI, 2 AO, 1 Pt100, 4 high-speed counters (60 kHz), integrated DP interface, Integr. power supply 24 V DC, work memory 192 KB, Front connector (2x 40-pole) and Micro Memory Card required



General information	
HW functional status	01
Firmware version	V3.3
Engineering with	
<ul style="list-style-type: none"> Programming package 	STEP 7 V5.5 + SP1 or higher or STEP 7 V5.3 + SP2 or higher with HSP 203
Supply voltage	
Rated value (DC)	
<ul style="list-style-type: none"> 24 V DC 	Yes
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
external protection for power supply lines (recommendation)	Miniature circuit breaker, type C; min. 2 A; miniature circuit breaker type B, min. 4 A
Mains buffering	
<ul style="list-style-type: none"> Mains/voltage failure stored energy time 	5 ms
<ul style="list-style-type: none"> Repeat rate, min. 	1 s
Load voltage L+	
Digital inputs	
— Rated value (DC)	24 V

— Reverse polarity protection	Yes
Digital outputs	
— Rated value (DC)	24 V
— Reverse polarity protection	No
Input current	
Current consumption (rated value)	880 mA
Current consumption (in no-load operation), typ.	150 mA
Inrush current, typ.	5 A
I^2t	0.7 A ² ·s
Digital inputs	
• from load voltage L+ (without load), max.	80 mA
Digital outputs	
• from load voltage L+, max.	50 mA
Power loss	
Power loss, typ.	13 W
Memory	
Work memory	
• integrated	192 kbyte
• expandable	No
• Size of retentive memory for retentive data blocks	64 kbyte
Load memory	
• Plug-in (MMC)	Yes
• Plug-in (MMC), max.	8 Mbyte
• Data management on MMC (after last programming), min.	10 y
Backup	
• present	Yes; Guaranteed by MMC (maintenance-free)
• without battery	Yes; Program and data
CPU processing times	
for bit operations, typ.	0.06 µs
for word operations, typ.	0.12 µs
for fixed point arithmetic, typ.	0.16 µs
for floating point arithmetic, typ.	0.59 µs
CPU-blocks	
Number of blocks (total)	1 024; (DBs, FCs, FBs); the maximum number of loadable blocks can be reduced by the MMC used.
DB	
• Number, max.	1 024; Number range: 1 to 16000
• Size, max.	64 kbyte
FB	

• Number, max.	1 024; Number range: 0 to 7999
• Size, max.	64 kbyte
FC	
• Number, max.	1 024; Number range: 0 to 7999
• Size, max.	64 kbyte
OB	
• Description	see instruction list
• Size, max.	64 kbyte
• Number of free cycle OBs	1; OB 1
• Number of time alarm OBs	1; OB 10
• Number of delay alarm OBs	2; OB 20, 21
• Number of cyclic interrupt OBs	4; OB 32, 33, 34, 35
• Number of process alarm OBs	1; OB 40
• Number of DPV1 alarm OBs	3; OB 55, 56, 57
• Number of startup OBs	1; OB 100
• Number of asynchronous error OBs	5; OB 80, 82, 85, 86, 87
• Number of synchronous error OBs	2; OB 121, 122
Nesting depth	
• per priority class	16
• additional within an error OB	4
Counters, timers and their retentivity	
S7 counter	
• Number	256
Retentivity	
— adjustable	Yes
— lower limit	0
— upper limit	255
— preset	Z 0 to Z 7
Counting range	
— lower limit	0
— upper limit	999
IEC counter	
• Number	Unlimited (limited only by RAM capacity)
S7 times	
• Number	256
Retentivity	
— adjustable	Yes
— lower limit	0
— upper limit	255
— preset	No retentivity
Time range	

— lower limit	10 ms
— upper limit	9 990 s
IEC timer	
• present	Yes
• Type	SFB
• Number	Unlimited (limited only by RAM capacity)
Data areas and their retentivity	
retentive data area in total	All, max. 64 KB
Flag	
• Number, max.	256 byte
• Retentivity available	Yes; MB 0 to MB 255
• Retentivity preset	MB 0 to MB 15
• Number of clock memories	8; 1 memory byte
Data blocks	
• Retentivity adjustable	Yes; via non-retain property on DB
• Retentivity preset	Yes
Local data	
• per priority class, max.	32 kbyte; Max. 2048 bytes per block
Address area	
I/O address area	
• Inputs	2 048 byte
• Outputs	2 048 byte
of which distributed	
— Inputs	2 003 byte
— Outputs	2 010 byte
Process image	
• Inputs	2 048 byte
• Outputs	2 048 byte
• Inputs, adjustable	2 048 byte
• Outputs, adjustable	2 048 byte
• Inputs, default	128 byte
• Outputs, default	128 byte
Default addresses of the integrated channels	
— Digital inputs	124.0 to 126.7
— Digital outputs	124.0 to 125.7
— Analog inputs	752 to 761
— Analog outputs	752 to 755
Digital channels	
• Inputs	16 048
— of which central	1 016
• Outputs	16 096

— of which central	1 008
Analog channels	
• Inputs	1 006
— of which central	253
• Outputs	1 007
— of which central	250
Hardware configuration	
Number of expansion units, max.	3
Number of DP masters	
• integrated	1
• via CP	4
Number of operable FMs and CPs (recommended)	
• FM	8
• CP, PtP	8
• CP, LAN	10
Rack	
• Racks, max.	4
• Modules per rack, max.	8; In rack 3 max. 7
Time of day	
Clock	
• Hardware clock (real-time)	Yes
• retentive and synchronizable	Yes
• Backup time	6 wk; At 40 °C ambient temperature
• Deviation per day, max.	10 s; Typ.: 2 s
• Behavior of the clock following POWER-ON	Clock continues running after POWER OFF
• Behavior of the clock following expiry of backup period	Clock continues to run with the time at which the power failure occurred
Operating hours counter	
• Number	1
• Number/Number range	0
• Range of values	0 to 2 ³¹ hours (when using SFC 101)
• retentive	Yes; Must be restarted at each restart
Clock synchronization	
• supported	Yes
• to MPI, master	Yes
• to MPI, slave	Yes
• to DP, master	Yes; With DP slave only slave clock
• to DP, slave	Yes
• in AS, master	Yes
• in AS, slave	No
Digital inputs	

Number of digital inputs	24
• of which inputs usable for technological functions	16
integrated channels (DI)	24
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Number of simultaneously controllable inputs	
horizontal installation	
— up to 40 °C, max.	24
— up to 60 °C, max.	12
vertical installation	
— up to 40 °C, max.	12
Input voltage	
• Rated value (DC)	24 V
• for signal "0"	-3 to +5V
• for signal "1"	+15 to +30V
Input current	
• for signal "1", typ.	8 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	Yes; 0.1 / 0.3 / 3 / 15 ms (You can reconfigure the input delay of the standard inputs during program runtime. Please note that under certain circumstances your newly set filter time may not be effective until the next filter cycle.)
— Rated value	3 ms
for counter/technological functions	
— at "0" to "1", max.	8 µs; Minimum pulse width/minimum pause between pulses at maximum counting frequency
Cable length	
• shielded, max.	1 000 m; 50 m for technological functions
• unshielded, max.	600 m; For technological functions: No
for technological functions	
— shielded, max.	50 m; at maximum count frequency
— unshielded, max.	not allowed
Digital outputs	
Number of digital outputs	16
• of which high-speed outputs	4; Notice: You cannot connect the fast outputs of your CPU in parallel
integrated channels (DO)	16
Short-circuit protection	Yes; Clocked electronically
• Response threshold, typ.	1 A
Limitation of inductive shutdown voltage to	L+ (-48 V)
Controlling a digital input	Yes

Switching capacity of the outputs	
• on lamp load, max.	5 W
Load resistance range	
• lower limit	48 Ω
• upper limit	4 k Ω
Output voltage	
• for signal "1", min.	L+ (-0.8 V)
Output current	
• for signal "1" rated value	500 mA
• for signal "1" permissible range, min.	5 mA
• for signal "1" permissible range, max.	0.6 A
• for signal "1" minimum load current	5 mA
• for signal "0" residual current, max.	0.5 mA
Parallel switching of two outputs	
• for uprating	No
• for redundant control of a load	Yes
Switching frequency	
• with resistive load, max.	100 Hz
• with inductive load, max.	0.5 Hz
• on lamp load, max.	100 Hz
• of the pulse outputs, with resistive load, max.	2.5 kHz
Total current of the outputs (per group)	
horizontal installation	
— up to 40 °C, max.	3 A
— up to 60 °C, max.	2 A
vertical installation	
— up to 40 °C, max.	2 A
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Analog inputs	
Number of analog inputs	
• For voltage/current measurement	4
• For resistance/resistance thermometer measurement	1
integrated channels (AI)	5; 4 x current/voltage, 1 x resistance
permissible input voltage for current input (destruction limit), max.	5 V; Permanent
permissible input voltage for voltage input (destruction limit), max.	30 V; Permanent
permissible input current for voltage input (destruction limit), max.	0.5 mA; Permanent

permissible input current for current input (destruction limit), max.	50 mA; Permanent
No-load voltage for resistance-type transmitter, typ.	3.3 V
Constant measurement current for resistance-type transmitter, typ.	1.25 mA
Technical unit for temperature measurement adjustable	Yes; Degrees Celsius / degrees Fahrenheit / Kelvin
Input ranges	
• Voltage	Yes; $\pm 10\text{ V}$ / 100 k Ω ; 0 V to 10 V / 100 k Ω
• Current	Yes; $\pm 20\text{ mA}$ / 100 Ω ; 0 mA to 20 mA / 100 Ω ; 4 mA to 20 mA / 100 Ω
• Resistance thermometer	Yes; Pt 100 / 10 M Ω
• Resistance	Yes; 0 Ω to 600 Ω / 10 M Ω
Input ranges (rated values), voltages	
• 0 to +10 V	Yes
• Input resistance (0 to 10 V)	100 k Ω
Input ranges (rated values), currents	
• 0 to 20 mA	Yes
• Input resistance (0 to 20 mA)	100 Ω
• -20 mA to +20 mA	Yes
• Input resistance (-20 mA to +20 mA)	100 Ω
• 4 mA to 20 mA	Yes
• Input resistance (4 mA to 20 mA)	100 Ω
Input ranges (rated values), resistance thermometer	
• Pt 100	Yes
• Input resistance (Pt 100)	10 M Ω
Input ranges (rated values), resistors	
• 0 to 600 ohms	Yes
• Input resistance (0 to 600 ohms)	10 M Ω
Thermocouple (TC)	
Temperature compensation	
— parameterizable	No
Characteristic linearization	
• parameterizable	Yes; by software
— for resistance thermometer	Pt 100
Cable length	
• shielded, max.	100 m
Analog outputs	
Number of analog outputs	2
integrated channels (AO)	2
Voltage output, short-circuit protection	Yes
Voltage output, short-circuit current, max.	55 mA

Current output, no-load voltage, max.	14 V
Output ranges, voltage	
• 0 to 10 V	Yes
• -10 V to +10 V	Yes
Output ranges, current	
• 0 to 20 mA	Yes
• -20 mA to +20 mA	Yes
• 4 mA to 20 mA	Yes
Connection of actuators	
• for voltage output two-wire connection	Yes; Without compensation of the line resistances
• for voltage output four-wire connection	No
• for current output two-wire connection	Yes
Load impedance (in rated range of output)	
• with voltage outputs, min.	1 k Ω
• with voltage outputs, capacitive load, max.	0.1 μ F
• with current outputs, max.	300 Ω
• with current outputs, inductive load, max.	0.1 mH
Destruction limits against externally applied voltages and currents	
• Voltages at the outputs towards MANA	16 V; Permanent
• Current, max.	50 mA; Permanent
Cable length	
• shielded, max.	200 m
Analog value generation for the inputs	
Measurement principle	Actual value encryption (successive approximation)
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	12 bit
• Integration time, parameterizable	Yes; 16.6 / 20 ms
• Interference voltage suppression for interference frequency f1 in Hz	50 / 60 Hz
• permissible input frequency, max.	400 Hz
• Time constant of the input filter	0.38 ms
• Basic execution time of the module (all channels released)	1 ms
Analog value generation for the outputs	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	12 bit
• Conversion time (per channel)	1 ms
Settling time	
• for resistive load	0.6 ms
• for capacitive load	1 ms

- for inductive load

0.5 ms

Encoder

Connection of signal encoders

- | | |
|---|---|
| • for voltage measurement | Yes |
| • for current measurement as 2-wire transducer | Yes; with external supply |
| • for current measurement as 4-wire transducer | Yes |
| • for resistance measurement with two-wire connection | Yes; Without compensation of the line resistances |
| • for resistance measurement with three-wire connection | No |
| • for resistance measurement with four-wire connection | No |

Connectable encoders

- | | |
|---|--------|
| • 2-wire sensor | Yes |
| — permissible quiescent current (2-wire sensor), max. | 1.5 mA |

Errors/accuracies

- | | |
|--|-----------|
| Temperature error (relative to input range), (+/-) | 0.006 %/K |
| Crosstalk between the inputs, min. | 60 dB |
| Repeat accuracy in steady state at 25 °C (relative to input range), (+/-) | 0.06 % |
| Output ripple (relative to output range, bandwidth 0 to 50 kHz), (+/-) | 0.1 % |
| Linearity error (relative to output range), (+/-) | 0.15 % |
| Temperature error (relative to output range), (+/-) | 0.01 %/K |
| Crosstalk between the outputs, min. | 60 dB |
| Repeat accuracy in steady state at 25 °C (relative to output range), (+/-) | 0.06 % |

Operational error limit in overall temperature range

- | | |
|--|-----|
| • Voltage, relative to input range, (+/-) | 1 % |
| • Current, relative to input range, (+/-) | 1 % |
| • Resistance, relative to input range, (+/-) | 1 % |
| • Voltage, relative to output range, (+/-) | 1 % |
| • Current, relative to output range, (+/-) | 1 % |

Basic error limit (operational limit at 25 °C)

- | | |
|--|-------------------------------------|
| • Voltage, relative to input range, (+/-) | 0.8 %; Linearity error ± 0.06 % |
| • Current, relative to input range, (+/-) | 0.8 %; Linearity error ± 0.06 % |
| • Resistance, relative to input range, (+/-) | 0.8 %; Linearity error ± 0.2 % |
| • Resistance thermometer, relative to input range, (+/-) | 0.8 % |
| • Voltage, relative to output range, (+/-) | 0.8 % |
| • Current, relative to output range, (+/-) | 0.8 % |

Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$, f_1 = interference frequency

- Series mode interference (peak value of interference < rated value of input range), min. 30 dB
- Common mode interference, min. 40 dB

Interfaces

Number of industrial Ethernet interfaces	0
Number of PROFINET interfaces	0
Number of RS 485 interfaces	2; MPI and PROFIBUS DP
Number of RS 422 interfaces	0

1. Interface

Interface type	Integrated RS 485 interface
Physics	RS 485
Isolated	No
Power supply to interface (15 to 30 V DC), max.	200 mA

Functionality	
• MPI	Yes
• PROFIBUS DP master	No
• PROFIBUS DP slave	No
• Point-to-point connection	No

MPI	
• Transmission rate, max.	187.5 kbit/s

Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	Yes
— S7 basic communication	Yes
— S7 communication	Yes; Only server, configured on one side
— S7 communication, as client	No; but via CP and loadable FB
— S7 communication, as server	Yes

2. Interface

Interface type	Integrated RS 485 interface
Physics	RS 485
Isolated	Yes
Power supply to interface (15 to 30 V DC), max.	200 mA

Functionality	
• MPI	No
• PROFINET IO Controller	No
• PROFINET IO Device	No
• PROFINET CBA	No
• PROFIBUS DP master	Yes
• PROFIBUS DP slave	Yes
• Point-to-point connection	No

DP master	
• Transmission rate, max.	12 Mbit/s
• Number of DP slaves, max.	124
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	No
— S7 basic communication	Yes; I blocks only
— S7 communication	Yes; Only server, configured on one side
— S7 communication, as client	No
— S7 communication, as server	Yes
— Equidistance	Yes
— Isochronous mode	No
— SYNC/FREEZE	Yes
— Activation/deactivation of DP slaves	Yes
— Number of DP slaves that can be simultaneously activated/deactivated, max.	8
— Direct data exchange (slave-to-slave communication)	Yes; As subscriber
— DPV1	Yes
Address area	
— Inputs, max.	2 kbyte
— Outputs, max.	2 kbyte
User data per DP slave	
— Inputs, max.	244 byte
— Outputs, max.	244 byte
DP slave	
• GSD file	The latest GSD file is available on the Internet (http://www.siemens.com/profibus-gsd)
• Transmission rate, max.	12 Mbit/s
• automatic baud rate search	Yes; only with passive interface
• Address area, max.	32
• User data per address area, max.	32 byte
Services	
— PG/OP communication	Yes
— Routing	Yes; Only with active interface
— Global data communication	No
— S7 basic communication	No
— S7 communication	Yes; Only server, configured on one side
— S7 communication, as client	No
— S7 communication, as server	Yes

— Direct data exchange (slave-to-slave communication)	Yes
— DPV1	No
Transfer memory	
— Inputs	244 byte
— Outputs	244 byte
Communication functions	
PG/OP communication	Yes
Data record routing	Yes
Global data communication	
• supported	Yes
• Number of GD loops, max.	8
• Number of GD packets, max.	8
• Number of GD packets, transmitter, max.	8
• Number of GD packets, receiver, max.	8
• Size of GD packets, max.	22 byte
• Size of GD packet (of which consistent), max.	22 byte
S7 basic communication	
• supported	Yes
• User data per job, max.	76 byte
• User data per job (of which consistent), max.	76 byte; 76 bytes (with X_SEND or X_RCV); 64 bytes (with X_PUT or X_GET as server)
S7 communication	
• supported	Yes
• as server	Yes
• as client	Yes; Via CP and loadable FB
• User data per job, max.	180 kbyte; With PUT/GET
• User data per job (of which consistent), max.	240 byte; as server
S5 compatible communication	
• supported	Yes; via CP and loadable FC
Number of connections	
• overall	12
• usable for PG communication	11
— reserved for PG communication	1
— adjustable for PG communication, min.	1
— adjustable for PG communication, max.	11
• usable for OP communication	11
— reserved for OP communication	1
— adjustable for OP communication, min.	1
— adjustable for OP communication, max.	11
• usable for S7 basic communication	8

- reserved for S7 basic communication 0
- adjustable for S7 basic communication, min. 0
- adjustable for S7 basic communication, max. 8
- usable for routing 4; max.

S7 message functions

Number of login stations for message functions, max.	12; Depending on the configured connections for PG/OP and S7 basic communication
Process diagnostic messages	Yes
simultaneously active Alarm-S blocks, max.	300

Test commissioning functions

Status block	Yes; Up to 2 simultaneously
Single step	Yes
Number of breakpoints	4

Status/control	
• Status/control variable	Yes
• Variables	Inputs, outputs, memory bits, DB, times, counters
• Number of variables, max.	30
— of which status variables, max.	30
— of which control variables, max.	14

Forcing	
• Forcing	Yes
• Forcing, variables	Inputs, outputs
• Number of variables, max.	10

Diagnostic buffer	
• present	Yes
• Number of entries, max.	500
— adjustable	No
— of which powerfail-proof	100; Only the last 100 entries are retained
• Number of entries readable in RUN, max.	499
— can be set	Yes; From 10 to 499
— preset	10

Service data	
• can be read out	Yes

Interrupts/diagnostics/status information

Diagnostics indication LED	
• Status indicator digital input (green)	Yes
• Status indicator digital output (green)	Yes

Integrated Functions

Number of counters	4; See "Technological Functions" manual
--------------------	---

Counting frequency (counter) max.	60 kHz
Frequency measurement	Yes
Number of frequency meters	4; up to 60 kHz (see "Technological Functions" manual)
controlled positioning	Yes
integrated function blocks (closed-loop control)	Yes; PID controller (see "Technological Functions" manual)
PID controller	Yes
Number of pulse outputs	4; Pulse width modulation up to 2.5 kHz (see "Technological Functions" Manual)
Limit frequency (pulse)	2.5 kHz

Potential separation

Potential separation digital inputs

- Potential separation digital inputs Yes
- between the channels No
- between the channels and backplane bus Yes

Potential separation digital outputs

- Potential separation digital outputs Yes
- between the channels Yes
- between the channels, in groups of 8
- between the channels and backplane bus Yes

Potential separation analog inputs

- Potential separation analog inputs Yes; common for analog I/O
- between the channels No
- between the channels and backplane bus Yes

Potential separation analog outputs

- Potential separation analog outputs Yes; common for analog I/O
- between the channels No
- between the channels and backplane bus Yes

Permissible potential difference

between different circuits	75 V DC/60 V AC
Between the inputs and MANA (UCM)	8 V DC
between MANA and M internally (UISO)	75 V DC/60 V AC

Isolation

Isolation tested with	600 V DC
-----------------------	----------

Ambient conditions

Ambient temperature during operation	
• min.	0 °C
• max.	60 °C

Configuration

Configuration software	
• STEP 7	Yes; STEP 7 V5.5 + SP1 or higher or STEP 7 V5.3 + SP2 or higher with HSP 203

• STEP 7 Lite	No
Programming	
• Command set	see instruction list
• Nesting levels	8
• System functions (SFC)	see instruction list
• System function blocks (SFB)	see instruction list
Programming language	
— LAD	Yes
— FBD	Yes
— STL	Yes
— SCL	Yes
— CFC	Yes
— GRAPH	Yes
— HiGraph®	Yes
Know-how protection	
• User program protection/password protection	Yes
• Block encryption	Yes; With S7 block Privacy
Dimensions	
Width	120 mm
Height	125 mm
Depth	130 mm
Weights	
Weight, approx.	680 g
last modified:	04/19/2018