

### Product description

PROFIBUS bus connector, RS485, Fast Connect, with PG socket, 90°  
 SIMATIC DP, Connection plug for PROFIBUS up to 12 Mbit/s 90°  
 cable outlet, Insulation displacement method FastConnect, With PG  
 receptacle 15.8x 59x 35.6 mm (BxHxD)



Suitability for use	For connecting PROFIBUS nodes to the PROFIBUS bus cable
<b>Transmission rate</b>	
Transfer rate / with PROFIBUS DP	9.6 kbit/s ... 12 Mbit/s
<b>Interfaces</b>	
Number of electrical connections	
• for PROFIBUS cables	2
• for network components or terminal equipment	1
Type of electrical connection	
• for PROFIBUS cables	Integrated insulation displacement contacts for 2-core PB FC-installation cables
• for network components or terminal equipment	9-pin Sub-D connector
Type of electrical connection / FastConnect	Yes
<b>Mechanical data</b>	
Design of terminating resistor	Integrated resistor combination that can be selected with slide switch
Material / of the enclosure	plastic
Locking mechanism design	Screw

### Design, dimensions and weight

Type of cable outlet	90 degree cable outlet
Width	15.8 mm
Height	59 mm
Depth	35.6 mm
Net weight	10 g

### Permitted ambient conditions

Ambient temperature	
• during operation	-25 ... +60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
Protection class IP	IP20

### Product properties, functions, components / general

Product feature	
• silicon-free	Yes
Product component	
• PG connection socket	Yes
• strain relief	Yes

### Standards, specifications, approvals

Certificate of suitability	
• RoHS conformity	Yes
• UL approval	Yes
<b>last modified:</b>	04/19/2018