

Product type designation

CP 5622

Communications processor CP 5622 PCI Express X1 card for Connection of a PG or PC with PCI Express bus to PROFIBUS or MPI can be used under 32 bit and 64 bit For operating systems also refer to Entry ID 22611503



Transmission rate

Transfer rate

- at the 1st interface / acc. to PROFIBUS 9.6 kbit/s ... 12 Mbit/s

Interfaces

Number of electrical connections

- at the 1st interface / acc. to PROFIBUS 1

Type of electrical connection

- at the 1st interface / acc. to PROFIBUS 9-pin Sub-D socket (RS 485)

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage

DC

Supply voltage

- 1 / from backplane bus 3.3 V
- 2 / from backplane bus 12 V

Relative symmetrical tolerance / at DC

- at 3.3 V 9 %
- at 12 V 8 %

Consumed current

• 1 / from backplane bus / at DC / maximum	0.3 A
• 2 / from backplane bus / at DC / maximum	0.25 A
Power loss [W]	4 W

Permitted ambient conditions

Ambient temperature	
• during operation	5 ... 55 °C
• during storage	-20 ... +60 °C
• during transport	-20 ... +60 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	85 %
Protection class IP	IP00

Design, dimensions and weight

Module format	PCI Express x1
Width	18 mm
Height	107 mm
Depth	101 mm
Net weight	87 g
Number of plug-in cards of same design / plug-in / per PC station	1
Number of units / Note	-

Performance data

Performance data / open communication

Software / for open communication / by means of SEND/RECEIVE / required	Yes, SOFTNET-PB DP / SOFTNET-PB DP Slave / SOFTNET-PB S7
Number of possible connections / for open communication / by means of SEND/RECEIVE / maximum	50

Performance data / PROFIBUS DP

Software / for DP master function / required	Yes, SOFTNET-PB DP
Service / as DP master	
• DPV0	Yes
• DPV1	Yes
• DPV2	No
Number of DP slaves / on DP master / usable	64
Amount of data	
• of the address area of the inputs / as DP master / total	14640 byte
• of the address area of the outputs / as DP master / total	14640 byte
• of the address area of the inputs / per DP slave	244 byte
• of the address area of the outputs / per DP slave	244 byte

<ul style="list-style-type: none"> • of the address area of the diagnostic data / per DP slave 	244 byte
Software / for DP slave function / required	Yes, SOFTNET-PB DP slave
Service / as DP slave	
<ul style="list-style-type: none"> • DPV0 • DPV1 	Yes No
Amount of data	
<ul style="list-style-type: none"> • of the address area of the inputs / as DP slave / total • of the address area of the outputs / as DP slave / total 	122 byte 122 byte

Performance data / S7 communication

Software / for S7 communication / required	Yes, SOFTNET-PB S7
Number of possible connections / for S7/PG communication / maximum	8

Performance data / multi-protocol mode

Number of configurable connections / per PC station	207
-----------------------------------------------------	-----

Product functions / management, configuration

Configuration software / required	Included in the scope of delivery of the required software product
-----------------------------------	--------------------------------------------------------------------

Product functions / Diagnosis

Product function	
<ul style="list-style-type: none"> • Port diagnostics 	Yes

Standards, specifications, approvals

Standard	
<ul style="list-style-type: none"> • for EMC • for safety / from CSA and UL • for emitted interference • for interference immunity 	2004/108/EC CAN/CSA C22.2 & UL 60950-1, UL 508 EN 61000-6-3, EN 61000-6-4 EN 61000-6-1, EN 61000-6-2
Certificate of suitability	
<ul style="list-style-type: none"> • CE marking • C-Tick 	Yes Yes

Accessories

accessories	optional: MPI cable
-------------	---------------------

Further Information / Internet Links

Internet-Link	
<ul style="list-style-type: none"> • to website: Selector SIMATIC NET SELECTION TOOL • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center 	http://www.siemens.com/snst http://www.siemens.com/simatic-net http://www.siemens.com/industrial-controls/mall http://www.siemens.com/industry/infocenter

- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

06/13/2018