

Product type designation

CP 342-5 FO

Communications processor CP 342-5 FO for connection of SIMATIC S7-300 to PROFIBUS DP, S5-compatible, PG/OP and S7 communication



Transmission rate

Transfer rate

- at the 1st interface / acc. to PROFIBUS

9.6 kbit/s ... 12 Mbit/s

Interfaces

Number of interfaces / acc. to Industrial Ethernet

0

Number of electrical connections

- for power supply

1

Number of optical interfaces / at the 1st interface / acc. to PROFIBUS

2

Design of the optical interface / at the 1st interface / acc. to PROFIBUS

Duplex socket

Type of electrical connection

- for power supply

4-pole terminal block

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage

DC

Supply voltage / 1 / from backplane bus

5 V

Supply voltage

24 V

Supply voltage / external

24 V

Supply voltage / external / at DC / Rated value	24 V
Relative positive tolerance / at DC / at 24 V	20 %
Relative negative tolerance / at DC / at 24 V	15 %
Consumed current	
• from backplane bus / at DC / at 5 V / typical	0.15 A
• from external supply voltage / at DC / at 24 V / typical	0.25 A
Power loss [W]	6 W

Permitted ambient conditions

Ambient temperature	
• during operation	0 ... 60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

Design, dimensions and weight

Module format	Compact module
Width	40 mm
Height	125 mm
Depth	120 mm
Net weight	0.3 kg
Mounting type	
• S7-300 rail mounting	Yes

Product properties, functions, components / general

Number of units	
• per CPU / maximum	4
Wire length	
• for PCF FOC / maximum	300 m
• for POF FOC / maximum	50 m

Performance data / open communication

Number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	16
Amount of data	
• as user data per connection / for open communication / by means of SEND/RECEIVE blocks / maximum	240 byte

Performance data / PROFIBUS DP

Service / as DP master	
• DPV0	Yes

Number of DP slaves / on DP master / usable	124
Amount of data	
<ul style="list-style-type: none"> • of the address area of the inputs / as DP master / total 	2160 byte
<ul style="list-style-type: none"> • of the address area of the outputs / as DP master / total 	2160 byte
<ul style="list-style-type: none"> • of the address area of the inputs / per DP slave 	244 byte
<ul style="list-style-type: none"> • of the address area of the outputs / per DP slave 	244 byte
<ul style="list-style-type: none"> • of the address area of the diagnostic data / per DP slave 	240 byte

Service / as DP slave	
<ul style="list-style-type: none"> • DPV0 	Yes

Amount of data	
<ul style="list-style-type: none"> • of the address area of the inputs / as DP slave / total 	240 byte
<ul style="list-style-type: none"> • of the address area of the outputs / as DP slave / total 	240 byte

Performance data / S7 communication

Number of possible connections / for S7 communication	
<ul style="list-style-type: none"> • maximum 	16

Performance data / multi-protocol mode

Number of active connections / with multi-protocol mode	
<ul style="list-style-type: none"> • without DP / maximum 	32
<ul style="list-style-type: none"> • with DP / maximum 	28

Performance data / telecontrol

Protocol / is supported	
<ul style="list-style-type: none"> • TCP/IP 	No
Configuration software	
<ul style="list-style-type: none"> • required 	STEP 7 V5.1 SP2 or higher / STEP 7 Professional V12 (TIA Portal) or higher

Accessories

Further Information / Internet Links

Internet-Link	
<ul style="list-style-type: none"> • to website: Selector SIMATIC NET SELECTION TOOL 	http://www.siemens.com/snst
<ul style="list-style-type: none"> • to website: Industrial communication 	http://www.siemens.com/simatic-net
<ul style="list-style-type: none"> • to website: Industry Mall 	https://mall.industry.siemens.com
<ul style="list-style-type: none"> • to website: Information and Download Center 	http://www.siemens.com/industry/infocenter
<ul style="list-style-type: none"> • to website: Image database 	http://automation.siemens.com/bilddb

- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

06/14/2018