Product data sheet Characteristics

9070T50D1 TRANSFORMER CONTROL 50VA 240/480V-120V

Product availability: Stock - Normally stocked in distribution facility





Price*: 116.00 USD



Main

Wall		
Product or component type	Industrial Control Transformer	
Power Rating	50 VA	
Primary Voltage	240 x 480 V	
	230 x 460 V	<u> </u>
	220 x 440 V	
Secondary Voltage	120 V	
	115 V	<u> </u>
	110 V	-
Туре	Т	

Complementary

Phase	1 phase	ă E
Power Rating	50 VA	
Primary to Secondary Voltage	220 x 440 V : 110 V 230 x 460 V : 115 V 240 x 480 V : 120 V	ion is not
Temperature rise	55 °C	
Electrical connection	Screw clamp terminals	Tischer in the state of the sta
Height	2.58 in	
Width	3 in	,, 9
Depth	3.09 in	<u> </u>
Material	Copper winding	
Fingersafe Cover Compatibility	FSC1	oi.

Environment

LITVITOTITICITE		Ś
Product certifications	CE	Ē
	UL listed file E61239	ne:
	CSA file LR37055 guide 184-N-90	clair
		i

Enclosure Type	Not rated (open device)
Insulation temperature	221 °F (105 °C)

Ordering and shipping details

Category	16200 - 9070 T (NOT TF) 50-200VA
Discount Schedule	CP8
GTIN	00785901904632
Nbr. of units in pkg.	1
Package weight(Lbs)	2.490000000000002
Returnability	Υ
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product		
RoHS (date code: YYWW)	Compliant - since 1227 - Schneider Electric declaration of conformity		
	Schneider Electric declaration of conformity		
REACh	Reference not containing SVHC above the threshold		
	Reference not containing SVHC above the threshold		
Product environmental profile	Available		
Product end of life instructions	Need no specific recycling operations		
California proposition 65	WARNING: This product can expose you to chemicals including:		
Substance 1	Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects other reproductive harm.		
More information	For more information go to www.p65warnings.ca.gov		

Contractual warranty

- Contractadi Harranty			
Warranty period	10 years		