



Main

Range of product	Modicon Premium Automation platform
Product or component type	Measurement and counter module
I/O modularity	2 channels
Electrical circuit type	Auxiliary output conforming to EN/IEC 61131-2

Complementary

Counting frequency	1000000 Hz
Incremental encoder frequency x1	500 kHz
Incremental encoder frequency x 4	250 kHz
Power dissipation in W	7...10 W
Cycle time	1 ms
Discrete input logic	Current sink auxiliary input (preset, enable and read) conforming to IEC 1131 Type 2 Resistive 2/3-wire proximity sensors PNP/NPN conforming to IEC 1131 Type 2 Resistive encoder input
Input logic	Positive
Input compatibility	Absolute encoder SSI serial output Incremental encoder 10...30 V totem pole Incremental encoder 5 V DC RS422 Absolute encoder parallel output ABE7CPA11
Input voltage	24 V 16 mA 2/3-wire proximity sensors PNP/NPN 24 V 8 mA auxiliary input (preset, enable and read) 5 V 18 mA encoder input
Input voltage limits	<= 5.5 V encoder input 19...30 V 2/3-wire proximity sensors PNP/NPN 19...30 V auxiliary input (preset, enable and read)
Voltage state 1 guaranteed	>= 11 V 2/3-wire proximity sensors PNP/NPN >= 11 V auxiliary input (preset, enable and read) >= 2.4 V encoder input
Current state 1 guaranteed	>= 6 mA 2/3-wire proximity sensors PNP/NPN >= 6 mA auxiliary input (preset, enable and read) >= 3.6 mA encoder input
Voltage state 0 guaranteed	<= 1.2 V encoder input <= 5 V 2/3-wire proximity sensors PNP/NPN <= 5 V auxiliary input (preset, enable and read)
Current state 0 guaranteed	<= 1 mA encoder input <= 2 mA 2/3-wire proximity sensors PNP/NPN

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

	<= 2 mA auxiliary input (preset, enable and read)
Response time	< 10 ms sensor voltage at return of 24 V auxiliary input (preset, enable and read) < 2.5 ms sensor voltage at loss of 24 V auxiliary input (preset, enable and read)
Input impedance	> 270 Ohm at U = 2.4 V encoder input 1500 Ohm at Un 2/3-wire proximity sensors PNP/NPN 3400 Ohm at Un auxiliary input (preset, enable and read) 400 Ohm at Un encoder input
Output voltage	24 V DC
Nominal output current	0.5 A
Output voltage limits	19...30 V
Voltage drop	< 0.5 V at state 1
Output compatibility	Positive logic DC inputs (resistance <= 15 kOhm) auxiliary output
Leakage current	< 0.1 mA
Switching time	< 0.250 ms
Switching frequency	< 0.6/LI ² Hz on inductive load
Output overload protection	Current limiter Thermal tripping via program or automatically
Output short-circuit protection	Current limiter Thermal tripping via program or automatically
Output overvoltage protection	Zener diode
Reverse polarity protection	Reverse diode on supply
Checks	Sensor power supply
Current consumption	15 mA 24 V DC 850 mA 5 V DC
Module format	Standard
Local signalling	2 LEDs green axis diagnostics available (CH.) 1 LED green module operating (RUN) 1 LED red external fault (I/O) 1 LED red internal fault, module failure (ERR)
Electrical connection	1 connector HE-10 20 pins 2 connectors SUB-D 15
Product weight	0.34 kg

Environment

Protective treatment	TC
Ambient air temperature for operation	0...60 °C
Ambient air temperature for storage	-25...70 °C
Relative humidity	5...95 % without condensation
Operating altitude	<= 2000 m

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0804 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------