



Main

Range of product	Modicon Premium Automation platform
Product or component type	Double-format PL7 processor
Software designation	PL7 Junior/Pro

Complementary


Concept	Transparent Ready
Number of racks	16 4/6/8 slots 8 12 slots
Number of slots	96 128 64
Discrete I/O processor capacity	2040 I/O
Analogue I/O processor capacity	256 I/O
Number of application specific channel	<= 64
Number of process control channel	<= 20 up to 60 simple loops
Integrated connection type	Fipio manager (127 agents) SUB-D 9 Ethernet TCP/IP RJ45 10/100 Mbit/s Non isolated serial link 2 female mini DIN 19.2/115 kbit/s
Communication module processor capacity	1 CANopen 4 network module 2 fieldbus modules (1 if CANopen used) 8 AS-Interface bus modules
Memory description	Internal RAM (with PCMCIA card) 176 Kwords data Internal RAM (without PCMCIA card) 96 Kwords program and data PCMCIA card 2048 Kwords additional data storage PCMCIA card 992 Kwords program
Maximum size of object areas	30.5 %MWi internal words located internal data 32 %KWw constant words located internal data 32768 %Mi located internal bits
Application structure	64 event tasks 1 fast task 1 master task
Execution time per instruction	0.06 µs Boolean with PCMCIA card 0.06 µs Boolean without PCMCIA card 0.08 µs word or fixed-point arithmetic with PCMCIA card 0.08 µs word or fixed-point arithmetic without PCMCIA card 1.7 µs floating points with PCMCIA card

	1.7 µs floating points without PCMCIA card
Number of instructions per ms	13.82 Kinst/ms 100 % Boolean with PCMCIA card 13.82 Kinst/ms 100 % Boolean without PCMCIA card 8.8 Kinst/ms 65 % Boolean + 35 % fixed arithmetic with PCMCIA card 8.8 Kinst/ms 65 % Boolean + 35 % fixed arithmetic without PCMCIA card
System overhead	0.22 ms fast task 1.15 ms master task
Marking	CE
Local signalling	1 LED green Ethernet TCP/IP port ready (RUN) 1 LED green processor running (RUN) 1 LED red activity on Fipio bus (FIP) 1 LED red collision detection (COL) 1 LED red Ethernet TCP/IP port fault (ERR) 1 LED red I/O module or configuration fault (I/O) 1 LED red processor or system fault (ERR) 1 LED yellow activity on the terminal port (TER) 1 LED yellow Ethernet link diagnostics (STS) 1 LED yellow reception activity (RX) 1 LED yellow transmission activity (TX)
Current consumption	1440 mA 5 V DC
Module format	Double

Environment

Standards	73/23/EEC 89/336/EEC 93/68/EEC CSA C22.2 No 213 Class I Division 2 Group A IEC 61131-2 CSA C22.2 No 213 Class I Division 2 Group D UL 508 92/31/EEC CSA C22.2 No 142 CSA C22.2 No 213 Class I Division 2 Group B CSA C22.2 No 213 Class I Division 2 Group C
Product certifications	ABS DNV BV RMRS RINA GL LR
Ambient air temperature for operation	0...60 °C
Ambient air temperature for storage	-25...70 °C
Relative humidity	10...95 % without condensation for operation 5...95 % without condensation for storage
Operating altitude	0...2000 m
Protective treatment	TC
IP degree of protection	IP20
Pollution degree	2

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0935 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------

TSXP574823AM is replaced by:



Standard environment BMEP583020

processor module M580 - Level 3 - Distributed

Qty 1

Reason for Substitution: End of life | Substitution date: 31 December 2018 | Not same dimensions/design - better performances, more services provided
