Product data sheet Characteristics

ZBVB54

orange light block for head Ø22 integral LED 24V plug-in connector

Price*: 57.00 USD

Schneider
Schneider
Electric

Z4V

DEL
18 mA

X2

ZBV-B33

Discontinued

ZBVB54 has not been replaced. Please contact your customer care center for more information.

| | | | ٠ | |
|---|---|---|---|---|
| N | Л | 2 | т | n |
| | | | | |

| | | ∵ |
|-------------------------------|----------------------------|----------|
| Range of product | Harmony XB5 Harmony XB4 | ilore r |
| Product or component type | Light block | 9 |
| Device short name | ZBV | ii. |
| Sale per indivisible quantity | 5 | ځ . |
| Connections - terminals | Plug-in connector | 9 |
| Signalling type | Steady | |
| Light source | Protected LED | ± |
| Bulb base | Integral LED | , All |
| Light block supply | Direct | <u></u> |
| Light source colour | Orange | |
| [Us] rated supply voltage | 24 V AC/DC, 50/60 Hz | |

Complementary

| - Complementary | | |
|-----------------------------|-------------------------------------|---|
| Product weight | 0.04 lb(US) (0.016 kg) | |
| Supply voltage limits | 19.230 V DC | |
| | 21.626.4 V AC | |
| Current consumption | 18 mA | |
| Service life | 100000 h at rated voltage and 25 °C | |
| Surge withstand | 1 kV conforming to IEC 61000-4-5 | |
| Mounting of block | Front mounting | |
| Electrical composition code | M1 | |
| | M2 | |
| | M3 | |
| | M4 | |
| | M5 | |
| | M6 | |
| | M10 | |
| | MF1 | |
| | P1 | ; |
| | P2 | |
| | PF1 | |
| Compatibility code | ZBV | |
| | | |

Environment

| Protective treatment | TH |
|---------------------------------------|--|
| Ambient air temperature for storage | -40158 °F (-4070 °C) |
| Ambient air temperature for operation | -40158 °F (-4070 °C) |
| IP degree of protection | IP20 conforming to IEC 60529 |
| Standards | EN/IEC 60947-5-1 CSA C22.2 No 14 EN/IEC 60947-5-5 JIS C 4520 UL 508 EN/IEC 60947-1 EN/IEC 60947-5-4 |
| Resistance to fast transients | 2 kV conforming to IEC 61000-4-4 |
| Resistance to electromagnetic fields | 9.14 V/yd (10 V/m) conforming to IEC 61000-4-3 |
| Resistance to electrostatic discharge | 6 kV on contact (on metal parts) conforming to IEC 61000-4-2 8 kV in free air (in insulating parts) conforming to IEC 61000-4-2 |
| Electromagnetic emission | Class B conforming to IEC 55011 |

Ordering and shipping details

| ordering and ompping dotaile | |
|------------------------------|---|
| Category | 22469 - PUSHBUTTON,22MM ACCESSORIES-NEW |
| Discount Schedule | CS2 |
| GTIN | 00785901374589 |
| Nbr. of units in pkg. | 5 |
| Package weight(Lbs) | 0.02 |
| Returnability | N |
| Country of origin | FR |

Offer Sustainability

| California proposition 65 | WARNING: This product can expose you to chemicals including: |
|---------------------------|--|
| Substance 1 | Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. |
| More information | For more information go to www.p65warnings.ca.gov |

Contractual warranty


| Warranty period | 18 months |
|-----------------|-----------|

Product data sheet Dimensions Drawings

ZBVB54

Dimensions

with ZB5AZ009 Fixing Collar



with ZB4BZ009 Fixing Collar

