



## Main

Range of product	OsiSense XC
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKE
Head type	Rotary head
Product compatibility	XCKJ
Associated lever	ZCKY11 ZCKY13 ZCKY14 ZCKY41 ZCKY43 ZCKY51 ZCKY52 ZCKY53 ZCKY59 ZCKY81 ZCKY91
Associated body	ZCKJ1 ZCKJ11 ZCKJ11H29 ZCKJ11H7 ZCKJ1H29 ZCKJ1H7 ZCKJ2 ZCKJ21 ZCKJ21H29 ZCKJ21H7 ZCKJ2H29 ZCKJ2H7 ZCKJ4 ZCKJ404 ZCKJ404H29 ZCKJ404H7 ZCKJ41 ZCKJ4104 ZCKJ4104H29 ZCKJ4104H7

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

ZCKJ41H29  
 ZCKJ41H7  
 ZCKJ4H29  
 ZCKJ4H7  
 ZCKJ5  
 ZCKJ5H29  
 ZCKJ5H7  
 ZCKJ6  
 ZCKJ6H29  
 ZCKJ6H7  
 ZCKJ7  
 ZCKJ7H29  
 ZCKJ7H7  
 ZCKJ8  
 ZCKJ8H29  
 ZCKJ8H7  
 ZCKJ9  
 ZCKJ9H29  
 ZCKJ9H7  
 ZCKJD31  
 ZCKJD31H29  
 ZCKJD31H7  
 ZCKJD35  
 ZCKJD35H29  
 ZCKJD35H7  
 ZCKJD37  
 ZCKJD37H29  
 ZCKJD37H7  
 ZCKJD39  
 ZCKJD39H29  
 ZCKJD39H7

Movement of operating head	Rotary
Type of operator	Without operating lever spring return
Type of approach	Lateral approach 1 or 2 programmable direction

### Complementary

Switch actuation	From left and/or right CW and/or CCW
Positive opening	With
Head material	Metal

### Environment

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
Environmental characteristic	Standard environment

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0851 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product end of life instructions	Need no specific recycling operations

### Contractual warranty

Warranty period	18 months
-----------------	-----------